



The
Garden
Niche®



DETAILED IN-GROUND NICHE INSTALLATION INSTRUCTIONS

1.- Choose and assess the placement spot.

First, we recommend you have the area where you will install the niche checked for underground water pipes, electricity cables, gas lines, sewer lines, drainpipes, or any other utility features that could be damaged during the installation of the In-Ground Niche. If you don't have any of this information with you, contact your local 811. "Call Before You Dig". You should also remember that there may be roots and rock to work around, as high-water flow areas.

2.- Install the Anchoring Rods

Required tools and materials:

- Anchoring rods
- In-Ground Niche Boddy

Screw the anchoring rods into the thread inserts at the bottom of the Niche.

3.- Mark your Digging Spot

Required tools:

- Inverted Marking Spray Paint or similar product.
- Niche body with the anchoring rods installed.

Once you locate where you will install your In-Ground Niche and make sure there are no underground utilities features at that spot, place the In-Ground Niche on the ground and mark a circumference around the niche, leaving an extra 2 to 3 inches all around the niche.

4.- Dig the Hole

Required tools:

- Shovel
- Post hole digger tool and /or auger.
- Gloves
- Measuring Tape

We're now ready to start digging. Take the shovel and dig "25 inches deep into the ground for a Large Double Deep In-Ground Niche; 13 inches deep into the ground for a Large Single Deep In-Ground Niche, or 8 inches deep into the ground for a Small Single Deep In-Ground Niche". With your post-hole digger's help, remove all the excessive dirt and mold the hole into a cylindrical shape.

Recommendations: Wear gloves at all times. Keep a wheelbarrow or similar container to put the dug-up dirt.

5.- Prep the hole and set the niche.

Required Tools and Materials:

- Quick drying concrete like QUIKRETE® Crack Resistant Concrete Mix or similar product
- Sand for leveling like QUIKRETE® All-Purpose Sand or similar product.
- Water
- Wood, plastic, metal, or similar material, sturdy rod
- Level
- Heavy-duty knife or scissors
- Small bucket, medium size jug, and small plastic cup
- Drying cloths





**The
Garden
Niche®**



- 5.1 - Pour into the hole enough sand to raise the bottom of the hole level about 1 inch. Use your hands or level to spread the sand evenly. Using the niche, pound the sand to compact it.
- 5.2 - Use the level to ensure the hole's bottom is leveled. Move the sand as needed.
- 5.3 - Place your In-Ground Niche centered in the hole.
- 5.4 - Use the level to make sure the niche is leveled.
- 5.5 - Pour the powder concrete mix evenly around the niche in the hole to cover 2" above the anchoring rods.
- 5.6 - Fill the entire space around the niche with water.
- 5.7 - Fill the niche with water to weigh it down and prevent shifting and floating.
- 5.8 - Gently stir and mix the concrete and water with the rod, making sure the niche is not shifted out of place.
- 5.9 - Use the level to make sure the niche is still leveled.
- 5.10 - Let the concrete set for 5 hours.
- 5.11 - Once the concrete is set, fill the entire space around the niche with the dirt you dug out.
- 5.12 - Compact the dirt as much as possible using a compacting tool or stomping with your feet. Keep pouring dirt until you reach ground level.
- 5.13 - Drain the niche using the small bucket, medium size jug, and small plastic cup.
- 5.14 - Dry the interior of the niche with drying cloths.

6. - Place the Urns

You can now place your urns inside the In-Ground Niche. In the case of the Large Double Deep model, you can start by placing the urns in the bottom chamber and then placing the chamber divider on the lip between the bottom and upper chambers. Once the divider is installed, you can place more urns in the upper chamber.

7. - Place the Granite Lid

Now is the time to cover your In-Ground Niche. For the Large In-Ground models, the granite lid weighs about 70 pounds. At least two people need to lift the lid and place it on top of the niche. The Small In-Ground model's lid weighs about 32 pounds, make sure you safely lift it and place it on top of the niche.

8.- Place the safety rosettes for the Premium Packages

Required Tools and materials:

- 1/4-inch socket screwdriver handle
- Security bronze rosettes (2)
- Tamper-proof screws (2)
- Tamper-proof bit

Once the lid is properly placed on the upper part of the niche, make sure the side holes of the lids are aligned with the thread inserts embedded in the side of the above-ground section of the niche. Insert the tamper-proof screws through the bronze rosettes and screw them into the thread inserts. Tighten as much with your hands and finish with the security bit and socket screwdriver handle. If one of the sides is completely tight, but the rosette is still loose, slide the lid to that side until there is no space between the lid and the rosette, and tighten the other side's screw.

